

Wall mounted unit

FTXTA-CW + RXTA-C



BLUEVOLUTION nepura stylish



Fireplace logic



Coanda effect - heating



Heat boost



Guaranteed operation down to -30°C



Onecta app

Where innovation meets creativity, even at ambient temperatures down to -30°C

- › Guaranteed heating capacity down to -30°C
- › Even temperature distribution thanks to fireplace logic
- › Compact design in matt crystal white
- › Perfect temperature distribution thanks to Coanda effect
- › Intelligent thermal sensor: air flow is adjusted when detecting temperature differences
- › Onecta app
- › Voice control

- › Bluevolution range: lower environmental impact
- › Seasonal efficiency values up to A+++ in cooling and heating
- › Daikin Flash Streamer technology: powerful air purification
- › Practically inaudible
- › Heat boost: fast heating during start-up (pair only)

FTXTA-CW + RXTA-C



Indoor unit		FTXTA		30CW
Dimensions	Unit	HeightxWidthxDepth	mm	295 x798 x189
Weight	Unit		kg	12
Air filter	Type			Removable / washable
Fan	Air flow rate	Cooling	Silent operation/ Low/Medium/High	m ³ /min
		Heating	Silent operation / Low / Medium / High	m ³ /min
				4.9 / 6.0 / 9.0 / 13.1
				5.0 / 5.8 / 8.2 / 12.3
Sound power level	Cooling		dBA	60.0
	Heating		dBA	60.0
Sound pressure level	Cooling	Silent operation/Low/High	dBA	20.0 / 25.0 / 43.0
	Heating	Silent operation/Low/High	dBA	19.0 / 24.0 / 41.0
Control systems	Infrared remote control			ARC466A84
	Wired remote control			BRC073A4


Cooling: indoor temp. 27°CDB, 19°CWB; outdoor temp. 35°CDB, 24°CWB; equivalent piping length: 5m | Heating: indoor temp. 20°CDB; outdoor temp. 7°CDB, 6°CWB; equivalent refrigerant piping: 5m | See separate drawing for electrical data

Outdoor unit		RXTA		30C
Dimensions	Unit	HeightxWidthxDepth	mm	605 x930 x376
Weight	Unit		kg	42
Sound power level	Cooling		dBA	60
	Heating		dBA	60
Sound pressure level	Cooling	Nom.	dBA	48.0
	Heating	Nom.	dBA	49.0
Operation range	Cooling	Ambient	Min.~Max.	°CDB
	Heating	Ambient	Min.~Max.	°CWB
Refrigerant	Type			R-32
	GWP			675.0
	Charge		kg/ TCO2Eq	0.97 / 0.66
Piping connections	Liquid	OD	mm	6.35
	Gas	OD	mm	9.50
	Piping length	OU - IU	Max.	m
	Additional refrigerant charge		kg/m	0.02 (for piping length exceeding 10m)
	Level difference	IU - OU	Max.	m
Power supply	Phase/Frequency/Voltage		Hz/V	1~/50 / 220-240
Current - 50Hz	Maximum fuse amps (MFA)		A	16

Contains fluorinated greenhouse gases | See separate drawing for operation range | See separate drawing for electrical data

Efficiency data		FTXTA + RXTA		30CW + 30C
Cooling capacity	Min./Nom./Max.		kW	1.2 / 3.0 / 4.6
Heating capacity	Min./Nom./Max.		kW	0.8 / 3.2 / 7.10
Power input	Cooling	Nom.	kW	0.62
	Heating	Nom.	kW	0.64
Space cooling	Energy efficiency class			A+++
	Capacity	Pdesign	kW	3.00
	SEER			8.75
	Annual energy consumption		kWh/a	120
Space heating (Average climate)	Energy efficiency class			A+++
	Capacity	Pdesign	kW	3.00
	SCOP/A			5.17
	Annual energy consumption		kWh/a	812
Space heating (Cold climate)	Energy efficiency class			A+
	Capacity	Pdesignh	kW	4.38
	Annual energy consumption		kWh/a	2,248
	SCOP/C			4.09
Nominal efficiency	EER			4.89
	COP			5.01
	Annual energy consumption		kWh	310
	Energy labeling Directive	Cooling/Heating		A/A
Current - 50Hz	Maximum fuse amps (MFA)		A	16

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · BE 0412 120 336 (Responsible Editor)



ECPEN23-062

08/2023



Daikin Europe N.V. participates in the ECP programmes for Fan Coil Units and Variable Refrigerant Flow systems. Daikin Applied Europe S.p.A. participates in the ECP programmes for Liquid Chilling Packages and Hydronic Heat Pumps. Check ongoing validity of certificate: www.eurovent-certification.com

The present publication is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. / Daikin Central Europe HandelsGmbH. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH have compiled the content of this publication to the best of their knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. / Daikin Central Europe HandelsGmbH explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this publication. All content is copyrighted by Daikin Europe N.V.